

includes gas supply valves connected to various gas sources. Further functions of the processor 116 such as to provide overshoot control, energy stability control and/or to monitor input energy to the discharge, are described in more detail at U.S. patent application no. 09/588,561, which is assigned to the same assignee and is hereby incorporated by reference.

As shown in Figure 6, the processor 116 preferably communicates with the solid-state or thyatron pulser module 104 and HV power supply 108, separately or in combination, the gas handling module 106, the optics modules 110 and/or 112, the diagnostic module 118, and an interface 124. The laser resonator which surrounds the laser chamber 102 containing the laser gas mixture includes optics module 110 including line-narrowing optics for a line narrowed excimer or molecular fluorine laser, which may be replaced by a high reflectivity mirror or the like in a laser system wherein either line-narrowing is not desired, or if line narrowing is performed at the front optics module 112, or a spectral filter external to the resonator is used for narrowing the linewidth of the output beam.

SOLID STATE PULSER MODULE

The laser chamber 102 contains a laser gas mixture and includes one or more preionization units (not shown) in addition to the pair of main discharge electrodes 103. Preferred main electrodes 103 are described at U.S. patent application no. 09/453,670 for photolithographic applications, which is assigned to the same assignee as the present application and is hereby incorporated by reference, and may be alternatively configured, e.g., when a narrow discharge width is not preferred. Other electrode configurations are set forth at U.S. patents no. 5,729,565 and 4,860,300, each of which is assigned to the same assignee, and alternative embodiments are set forth at U.S. patents no. 4,691,322, 5,535,233 and 5,557,629, all of which are hereby incorporated by reference. Preferred preionization units may be sliding surface or corona-type and are described U.S. patent applications no. 09/922,241 and 09/532,276 (sliding surface) and 09/692,265 and 09/247,887

(corona discharge), each of which is assigned to the same assignee as the present application, and additional alternative embodiments are set forth at U.S. patents no. 5,337,330, 5,818,865, 5,875,207 and 5,991,324, and German Gebrauchsmuster DE 295 21 572 U1, all of the above patents and patent applications being hereby incorporated by reference.

The solid-state or thyatron pulser module 104 and high voltage power supply 108 supply electrical energy in compressed electrical pulses to the preionization and main electrodes 103 within the laser chamber 102 to energize the gas mixture. Components of the preferred pulser module and high voltage power supply are described above, and further details may be described at U.S. patent applications 09/640,595, 09/838,715, 60/204,095, 09/432,348 and 09/390,146, and U.S. patents no. 6,005,880, 6,226,307 and 6,020,723, each of which is assigned to the same assignee as the present application and which is hereby incorporated by reference into the present application. Other alternative pulser modules are described at U.S. patents no. 5,982,800, 5,982,795, 5,940,421, 5,914,974, 5,949,806, 5,936,988, 6,028,872, 6,151,346 and 5,729,562, each of which is hereby incorporated by reference.

RESONATOR, GENERAL

The laser resonator which surrounds the laser chamber 102 containing the laser gas mixture includes optics module 110 preferably including line-narrowing optics for a line narrowed excimer or molecular fluorine laser such as for photolithography, which may be replaced by a high reflectivity mirror or the like in a laser system wherein either line-narrowing is not desired (for TFT annealing, e.g.), or if line narrowing is performed at the front optics module 112, or a spectral filter external to the resonator is used, or if the line-narrowing optics are disposed in front of the HR mirror, for narrowing the bandwidth of the output beam. For an F₂-laser, optics for selecting one of multiple lines around 157 nm may be used, e.g., one or more dispersive prisms, birefringent plates or blocks and/or an interferometric device such as

an etalon or a device having a pair of opposed, non-parallel plates such as described in the 09/715,803 and 60/280,398 applications, wherein the same optic or optics or an additional line-narrowing optic or optics for narrowing the selected line may be used. Also, particularly for the F₂-laser, and also possibly for other excimer lasers, the total gas mixture pressure may be lower than conventional systems, e.g., lower than 3 bar, for producing the selected line at a narrow bandwidth such as 0.5 pm or less without using additional line-narrowing optics (see U.S. patent application no. 09/883,128, which is assigned to the same assignee as the present application and is hereby incorporated by reference).

The laser chamber 102 is sealed by windows transparent to the wavelengths of the emitted laser radiation 120. The windows may be Brewster windows or may be aligned at another angle, e.g., 5°, to the optical path of the resonating beam. One of the windows may also serve to output couple the beam or as a highly reflective resonator reflector on the opposite side of the chamber 102 as the beam is outcoupled.

DIAGNOSTIC MODULE

After a portion of the output beam 120 passes the outcoupler of the optics module 112, that output portion preferably impinges upon a beam splitter module 121 which includes optics for deflecting a portion 122 of the beam to the diagnostic module 118, or otherwise allowing a small portion 122 of the outcoupled beam to reach the diagnostic module 118, while a main beam portion 120 is allowed to continue as the output beam 120 of the laser system (see U.S. patent applications no. 09/771,013, 09/598,552, and 09/712,877 which are assigned to the same assignee as the present invention, and U.S. patent no. 4,611,270, each of which is hereby incorporated by reference. Preferred optics include a beamsplitter or otherwise partially reflecting surface optic. The optics may also include a mirror or beam splitter as a second reflecting optic. More than one beam splitter and/or HR mirror(s), and/or dichroic mirror(s) may be used to direct